

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
15 November 2001 (15.11.2001)

PCT

(10) International Publication Number
WO 01/86851 A2

- (51) International Patent Classification⁷: **H04L** [GB/GB]; 16 Kynges Mill Close, Frenchay, Bristol BS16 1JL (GB).
- (21) International Application Number: PCT/GB01/01968
- (22) International Filing Date: 8 May 2001 (08.05.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0011225.0 10 May 2000 (10.05.2000) GB
- (71) Applicant (for all designated States except US):
HEWLETT-PACKARD COMPANY [US/US]; 3000 Hanover Street, Palo Alto, CA 94304 (US).
- (74) Agent: **SQUIBBS, Robert, Francis**; Hewlett-Packard Limited, Intellectual Property Section, Filton Road, Stoke Gifford, Bristol BS34 8QZ (GB).
- (81) Designated States (national): JP, US.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- Published:**
— without international search report and to be republished upon receipt of that report
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **PANSON, Colin**
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CHARGING FOR VAS RESOURCE USAGE IN A COMMUNICATIONS INFRASTRUCTURE



(57) Abstract: A method is provided for charging for resource usage in a communications infrastructure. User packet-data traffic is divided into a first traffic flow (53) associated with value-added service, VAS, resources (54, 55) provided by the communications infrastructure, and a second traffic flow (51) for other traffic. The first traffic flow (53) is routed through a VAS marshalling system (60) where the respective traffic components for the individual VAS resources (54, 55) are identified and metered.

WO 01/86851 A2

Charging for VAS Resource Usage in a Communications Infrastructure

Field of the Invention

- 5 The present invention relates to charging for the use of communications-infrastructure resources including resources associated with value-added services (VAS).

Background of the Invention

- 10 Communication infrastructures suitable for mobile users (in particular, though not exclusively, cellular radio infrastructures) have now become widely adopted. Whilst the primary driver has been mobile telephony, the desire to implement mobile data-based services over these infrastructures, has led to the rapid development of data-capable bearer services across such infrastructures. This has opened up the possibility of many Internet-based services being available to mobile users.

- 15 By way of example, Figure 1 shows one form of known communication infrastructure for mobile users providing both telephony and data-bearer services. In this example, a mobile entity 20, provided with a radio subsystem 22 and a phone subsystem 23, communicates with the fixed infrastructure of GSM PLMN (Public Land Mobile Network) 10 to provide
- 20 basic voice telephony services. In addition, the mobile entity 20 includes a data-handling subsystem 25 interworking, via data interface 24, with the radio subsystem 22 for the transmission and reception of data over a data-capable bearer service provided by the PLMN; the data-capable bearer service enables the mobile entity 20 to communicate with a service system 40 connected to the public Internet 39. The data handling subsystem 25
- 25 supports an operating environment 26 in which applications run, the operating environment including an appropriate communications stack.

- More particularly, the fixed infrastructure 10 of the GSM PLMN comprises one or more Base Station Subsystems (BSS) 11 and a Network and Switching Subsystem NSS 12. Each
- 30 BSS 11 comprises a Base Station Controller (BSC) 14 controlling multiple Base Transceiver Stations (BTS) 13 each associated with a respective "cell" of the radio network. When active, the radio subsystem 22 of the mobile entity 20 communicates via a

radio link with the BTS 13 of the cell in which the mobile entity is currently located. As regards the NSS 12, this comprises one or more Mobile Switching Centers (MSC) 15 together with other elements such as Visitor Location Registers 32 and Home Location Register 32.

5

When the mobile entity 20 is used to make a normal telephone call, a traffic circuit for carrying digitised voice is set up through the relevant BSS 11 to the NSS 12 which is then responsible for routing the call to the target phone (whether in the same PLMN or in another network).

10

With respect to data transmission to/from the mobile entity 20, in the present example three different data-capable bearer services are depicted though other possibilities exist. A first data-capable bearer service is available in the form of a Circuit Switched Data (CSD) service; in this case a full traffic circuit is used for carrying data and the MSC 32 routes the circuit to an InterWorking Function IWF 34 the precise nature of which depends on what is connected to the other side of the IWF. Thus, IWF could be configured to provide direct access to the public Internet 39 (that is, provide functionality similar to an IAP - Internet Access Provider IAP). Alternatively, the IWF could simply be a modem connecting to a PSTN; in this case, Internet access can be achieved by connection across the PSTN to a standard IAP.

20

A second, low bandwidth, data-capable bearer service is available through use of the Short Message Service that passes data carried in signalling channel slots to an SMS unit which can be arranged to provide connectivity to the public Internet 39.

25

A third data-capable bearer service is provided in the form of GPRS (General Packet Radio Service) which enables IP (or X.25) packet data to be passed from the data handling system of the mobile entity 20, via the data interface 24, radio subsystem 21 and relevant BSS 11, to a GPRS network 17 of the PLMN 10 (and vice versa). The GPRS network 17 includes a SGSN (Serving GPRS Support Node) 18 interfacing BSC 14 with the network 17, and a GGSN (Gateway GPRS Support Node) interfacing the network 17 with an external network (in this example, the public Internet 39). Full details of GPRS can be found in the

30

ETSI (European Telecommunications Standards Institute) GSM 03.60 specification. Using GPRS, the mobile entity 20 can exchange packet data via the BSS 11 and GPRS network 17 with entities connected to the public Internet 39.

- 5 The data connection between the PLMN 10 and the Internet 39 will generally be through a firewall 35 with proxy and/or gateway functionality.

Different data-capable bearer services to those described above may be provided, the described services being simply examples of what is possible.

10

In Figure 1, a service system 40 is shown connected to the Internet 40, this service system being accessible to the OS/application 26 running in the mobile entity by use of any of the data-capable bearer services described above. The data-capable bearer services could equally provide access to a service system that is within the domain of the PLMN operator
15 or is connected to another public or private data network.

- With regard to the OS/application software 26 running in the data handling subsystem 25 of the mobile entity 20, this could, for example, be a WAP application running on top of a WAP stack where "WAP" is the Wireless Application Protocol standard. Details of WAP
20 can be found, for example, in the book "Official Wireless Application Protocol" Wireless Application Protocol Forum, Ltd published 1999 Wiley Computer Publishing. Where the OS/application software is WAP compliant, the firewall will generally also serve as a WAP proxy and gateway. Of course, OS/application 26 can comprise other functionality (for example, an e-mail client) instead of, or additional to, the WAP functionality.

25

- The mobile entity 20 may take many different forms. For example, it could be two separate units such as a mobile phone (providing elements 22-24) and a mobile PC (data-handling system 25) coupled by an appropriate link (wireline, infrared or even short range radio system such as Bluetooth). Alternatively, mobile entity 20 could be a single unit such as a
30 mobile phone with WAP functionality. Of course, if only data transmission/reception is required (and not voice), the phone functionality 24 can be omitted; an example of this is a PDA with built-in GSM data-capable functionality whilst another example is a digital

camera (the data-handling subsystem) also with built-in GSM data-capable functionality enabling the upload of digital images from the camera to a storage server.

5 Whilst the above description has been given with reference to a PLMN based on GSM technology, it will be appreciated that many other cellular radio technologies exist and can typically provide the same type of functionality as described for the GSM PLMN 10.

10 With respect to the billing of users for use of PLMN resources, network resource usage is tracked at key points (for example, the MSC) which generate billing records for billable events, these records being passed back to a central billing system 38. The amount a user is charged for using a resource will depend not only on how long a particular resource (e.g. voice traffic circuit) has been used, but also on factors such as time of day and quality of service.

15 More particularly, billing in relation to the GPRS network is effected by having the service nodes 18, 19 generate packet counts in respect of a user's use of the network, these packet counts then being passed to a charging gateway 37 that generates Call Detail Records for sending to the billing system 38.

20 It is also known to bill for usage of a WAP gateway.

It is an object of the present invention to facilitate the billing of value added services.

25

Summary of the Invention

According to the present invention, there is provided a method of charging for resource usage in a communications infrastructure, wherein user packet-data traffic is divided into a
30 first traffic flow associated with value-added service, VAS, resources provided by the communications infrastructure, and a second traffic flow for other traffic; the first traffic

flow being routed through a VAS marshalling system where the respective traffic components for the individual VAS resources are identified and metered.

According to a further aspect of the present invention, there is provided a packet-data
5 communications infrastructure including:

- a switch for dividing user packet-data traffic into a first traffic flow associated with value-added service, VAS, resources provided or accessible by the communications infrastructure, and a second traffic flow for other traffic; and
- a VAS marshalling system through which the first traffic flow is routed by the
10 switch, the marshalling system being operative to identify and meter the respective traffic components for the individual VAS resources.

Brief Description of the Drawings

A method and communications infrastructure, both embodying the present invention, for
15 charging for use of VAS-associated resources in a communications infrastructure, will now be described, by way of non-limiting example, with reference to the accompanying diagrammatic drawings, in which:

- . **Figure 1** is a diagram of a known communications infrastructure usable for transferring voice and data to/from a mobile entity; and
- 20 . **Figure 2** is a diagram illustrating how users are charged for VAS-associated resources accessed through a GPRS network of the Figure 1 communications infrastructure.

Best Mode of Carrying Out the Invention

The present invention is described hereinafter in relation to usage of particular resources accessed through GPRS network 17 of the Figure 1 system. For simplicity, no description is given as to how a user pays for use of the PLMN 10 other than GPRS network 17, it being possible to use any appropriate charging mechanism for such use.

30

With reference to Figure 2, the GPRS network 17 standardly comprises SGSN node 18, GGSN node 19, and charging gateway 37. User packet-data traffic through the GPRS

6

network is metered (packet counted) at nodes 18 and 19 and the counts passed to the charging node; the charging node 37 is responsible for sending Call Data Records to the billing system 38 in respect of these counts of user traffic flows.

- 5 In order to provide for more targeted charging in respect of the usage of specific resources, such as web proxy 54, e-mail server 55, and WAP gateway (not shown), the basic user traffic flow is divided by switching node 50 into a standard traffic flow 51 that, for example, is routed to an ISP 52, and a VAS traffic flow 53 that is routed to a VAS marshalling system 60. The division of the user traffic into flows 51 and 53 can simply be
10 done on the basis of whether individual data packets are destined for a VAS resource. Of course, for data packets coming from the VAS resources, the switching node simply routes the packets towards the appropriate mobile user.

- In marshalling system 60, the traffic flow components intended for, or coming from, each
15 different VAS resource are identified and metered (using, for example, Smart Internet Usage equipment commercially available from Hewlett-Packard Company). The metering information (including resource identifier) are passed to the billing system 38 to enable the user to be billed for the resource usage.

- 20 The above-described VAS billing system can be used not only to bill in respect of VAS resource usage in terms of usage of resources 54, 55 but also in dependence on the final, remote, resource concerned (for example, the identity of a web site being accessed). Additionally, the marshalling system can also include access control equipment providing, for example, payment-dependent access control to particular websites; a suitable system for
25 implementing such control is the Internet Payment System available from Verifone which can be set up to enable credit card payment to be made for website usage.

- The VAS billing system can be used to provide discounts and to split billing between the mobile user and the party controlling the other end point of the communication. Thus, a
30 party running a web site can contract with the PLMN operator to pick up part of the cost of accesses to their website made by mobile users.

5

The marshalling system 60 can be implemented either as one (or several) nodes configured as depicted in Figure 2 or as a group of distributed devices each associated with a respective one of the resources 54, 55.

- 10 It will be understood that the above-described method and system can be applied to the operation of other communication infrastructures and are not limited to use with GPRS networks.

15

CLAIMS

1. A method of charging for resource usage in a communications infrastructure, wherein
5 user packet-data traffic is divided into a first traffic flow associated with value-added service, VAS, resources provided by, or accessible to, the communications infrastructure, and a second traffic flow for other traffic; the first traffic flow being routed through a VAS marshalling system where the respective traffic components for the individual VAS resources are identified and metered.
- 10 2. A method according to claim 1, wherein all the user traffic is metered and billed at a prevailing charge rate, additional billing being effected in respect of use of the VAS resources by the first traffic flow as metered by the VAS marshalling system.
- 15 3. A method according to claim 1, wherein the VAS marshalling system separates / combines the component traffic flows associated with the various VAS resources.
4. A method according to claim 1, wherein the marshalling system is distributed across metering units associated with respective ones of said VAS resources, the first data flow
20 being formed from / divided into component traffic flows associated with respective ones of said VAS resources, externally of the distributed VAS marshalling system.
5. A method according to claim 1, wherein the billing in respect of a traffic component associated with a given VAS resource is divided between the user and the party responsible
25 for the traffic.
6. A packet-data communications infrastructure including:
 - a switch for dividing user packet-data traffic into a first traffic flow associated with value-added service, VAS, resources provided or accessible by the communications
30 infrastructure, and a second traffic flow for other traffic; and

- a VAS marshalling system through which the first traffic flow is routed by the switch, the marshalling system being operative to identify and meter the respective traffic components for the individual VAS resources.
- 5 7. An infrastructure according to claim 6, further including a standard-billing system for metering and billing all the user traffic at a prevailing charge rate, additional billing being effected in respect of use of the VAS resources by the first traffic flow as metered by the VAS marshalling system.
- 10 8. An infrastructure according to claim 6, wherein the VAS marshalling system is operative to separate / combine the component traffic flows associated with the various VAS resources.
- 15 9. An infrastructure according to claim 6, wherein the marshalling system is distributed across metering units associated with respective ones of said VAS resources, the infrastructure including a switch arrangement for forming / dividing the first data flow in from / into component traffic flows associated with respective ones of said VAS resources, externally of the distributed VAS marshalling system.
- 20 10. An infrastructure according to claim 6, wherein the marshalling system includes a sub-system for dividing the billing in respect of a traffic component associated with a given VAS resource, between the user and the party responsible for the traffic.

1/2





Figure 1
(Prior Art)

2/2

Figure 2



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 November 2001 (15.11.2001)

PCT

(10) International Publication Number
WO 01/086851 A3

(51) International Patent Classification⁷: H04M 15/00,
H04L 12/14, H04Q 7/00

(74) Agent: SQUIBBS, Robert, Francis; Hewlett-Packard
Limited, Intellectual Property Section, Filton Road, Stoke
Gifford, Bristol BS34 8QZ (GB).

(21) International Application Number: PCT/GB01/01968

(81) Designated States (*national*): JP, US.

(22) International Filing Date: 8 May 2001 (08.05.2001)

(84) Designated States (*regional*): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0011225.0 10 May 2000 (10.05.2000) GB

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(71) Applicant (*for all designated States except US*):
HEWLETT-PACKARD COMPANY [US/US]; 3000
Hanover Street, Palo Alto, CA 94304 (US).


(88) Date of publication of the international search report:
1 August 2002

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): P'ANSON, Colin
[GB/GB]; 16 Kynges Mill Close, Frenchay, Bristol BS16
1JL (GB).

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: METHOD OF CHARGING FOR RESOURCE USAGE IN A GPRS NETWORK



(57) Abstract: A method is provided for charging for resource usage in a communications infrastructure. User packet-data traffic is divided into a first traffic flow (53) associated with value-added service, VAS, resources (54, 55) provided by the communications infrastructure, and a second traffic flow (51) for other traffic. The first traffic flow (53) is routed through a VAS marshalling system (60) where the respective traffic components for the individual VAS resources (54, 55) are identified and metered.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 01/01968

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04M15/00 H04L12/14 H04Q7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L H04Q H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 26739 A (NOKIA TELECOMMUNICATIONS OY ;KARI HANNU H (FI); HAEMAELEINEN JARI) 24 July 1997 (1997-07-24) page 3, line 5 -page 4, line 30 ---	1-10
A	PIROT J: "IMPLEMENTATION OF VALUEADDED SERVICES IN AN INTERNET ENVIRONMENT VALUE-ADDED NETWORK SERVICES ARE ESSENTIAL IN THE ACCESS INFRASTRUCTURE IF THE INTERNET IS TO FULLY EXPLOIT ITS STRONG COMMERCIAL POTENTIAL" ELECTRICAL COMMUNICATION, ALCATEL. BRUSSELS, BE, 1 October 1997 (1997-10-01), pages 268-273, XP000751418 ISSN: 0013-4252 page 273, left-hand column, line 1 -middle column, line 31 --- -/--	1-10

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

27 May 2002

Date of mailing of the international search report

04/06/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Patlaka, E.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 01/01968

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	WO 00 79741 A (ERICSSON TELEFON AB L M) 28 December 2000 (2000-12-28) page 3, line 16 -page 4, line 21 -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 01/01968

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9726739	A	24-07-1997	FI 960185 A	16-07-1997
			AU 713041 B2	25-11-1999
			AU 1445897 A	11-08-1997
			EP 0875108 A1	04-11-1998
			WO 9726739 A1	24-07-1997
			JP 2000503825 T	28-03-2000
<hr/>				
WO 0079741	A	28-12-2000	AU 5862400 A	09-01-2001
			AU 5862500 A	09-01-2001
			EP 1188281 A1	20-03-2002
			EP 1188292 A2	20-03-2002
			WO 0079741 A1	28-12-2000
			WO 0079756 A2	28-12-2000
<hr/>				